

WHAT IS CLAIMED IS:

1. An apparatus operable to facilitate add/drop multiplexing of optical signals, the apparatus comprising:

5 an input operable to receive an input optical signal and an added optical signal, and to generate a first and a second copy of the input signal and a first and a second copy of the added signal;

002227 2284250  
0974633 43300  
10 a plurality of at least substantially reflective surfaces, each operable to receive either the first signal copies or the second signal copies and to reflect the copies for ultimate combination at an output to form an output signal for transmission, at least one of the at least substantially reflective surfaces comprising a  
15 moveable mirror operable to change its position relative to the input to create a phase shift between the first and second signal copies so that either the input optical signal or the added optical signal is communicated as the output signal depending on the position of the at least  
20 one moveable mirror.

2. The apparatus of Claim 1, wherein at least one of the at least substantially reflective surfaces comprises a micro-electro-optic system (MEMS) device  
25 operable to undergo a substantially piston-like motion to change its position relative to the input.

104

3. The apparatus of Claim 2, wherein the MEMS device comprises:

an inner conductive layer disposed inwardly from the moveable mirror layer and forming a space between the  
5 moveable mirror layer and the inner conductive layer;

wherein the moveable mirror layer comprises an at least substantially conductive layer operable to move relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and  
10 the inner conductive layer.

4. The apparatus of Claim 3, wherein the inner conductive layer comprises a doped semiconductor substrate.  
15

5. The apparatus of Claim 3, wherein the inner conductive layer comprises a layer of at least substantially conductive material formed outwardly from a semiconductor substrate.  
20

6. The apparatus of Claim 3, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror strips separated by air gaps operable to relieve air  
25 damping when the mirror strips move relative to the inner conductive layer.

7. The apparatus of Claim 6, wherein all of the moveable mirror strips move at least substantially in  
30 unison in response to the voltage difference.

09746823 13300  
00227 228460

105

8. The apparatus of Claim 7, wherein either the inner conductive layer or each of the moveable mirror strips is coupled to a ground, and wherein the other is operable to receive a control voltage signal.

5

9. The apparatus of Claim 3, wherein a grazing angle between the moveable mirror layer and the signal copy reflected by the moveable mirror layer comprises an angle that is less than forty-five degrees.

10

10. The apparatus of Claim 3, further comprising a second MEMS device disposed between the first MEMS device and the output, the second MEMS device comprising a moveable mirror layer operable to receive a phase shifted signal copy from the first MEMS device and to change its position relative to the first MEMS device to introduce a further phase shift to the signal copy.

15

11. The apparatus of Claim 1, wherein the input comprises a first beam splitter and wherein the output comprises a second beam splitter.

20

12. The apparatus of Claim 1, wherein the input and the output comprise a single beam splitting device.

25

002221-2224-60

13. The apparatus of Claim 11, further comprising at least one additional reflective surface between the beam splitter and the first MEMS device, the at least one additional reflective surface operable to receive a signal copy from the first beam splitter and to reflect the signal copy for ultimate reception by the first mirror.

[illegible]

a drop phase shift stage operable to receive an  
5 input optical signal and to either drop the input signal  
or to pass the optical signal toward an output, the drop  
phase shift stage comprising an at least substantially  
reflective surface operable to change its position to  
affect whether the input signal is dropped or passed to  
10 the output; and

15. The apparatus of Claim 14, wherein at least one  
20 of the at least substantially reflective surfaces  
comprises a moveable mirror layer of a micro-electro-  
optic system (MEMS) device operable to undergo a  
substantially piston-like motion to change its position.

a beam splitter operable to receive the input signal and communicate at least two copies of the signal in at least two directions; and

10 wherein at least one of the at least substantially  
reflective surfaces comprises a moveable mirror layer of  
a first micro-electro-optic system (MEMS) device, the  
moveable mirror layer operable to experience a  
substantially piston-like motion to change its position  
15 relative to the beam splitter, the change in position  
causing a phase shift between the signal copies and a  
corresponding interference between the signal copies at  
the output, the input signal being either passed to the  
add phase shift stage or dropped, depending on the  
20 position of the moveable mirror.

17. The apparatus of Claim 14, wherein the add phase shift stage comprises:

5 a beam splitter operable to receive either the added input signal or the input signal passed from the drop phase shift stage, the beam splitter further operable to communicate at least two copies of the received signal in at least two directions; and

10 a plurality of at least substantially reflective surfaces, each operable to receive one of the signal copies and to reflect the copies for ultimate combination at an output to form an output signal;

15 wherein at least one of the at least substantially reflective surfaces comprises a moveable mirror layer of a first micro-electro-optic system (MEMS) device, the moveable mirror layer operable to experience a substantially piston-like motion to change its position relative to the beam splitter, the change in position causing a phase shift between the signal copies to result in the received signal being communicated through the  
20 output of the add phase shift stage.

18. The apparatus of Claim 14, wherein the at least substantially reflective surfaces of the add phase shift stage and the drop phase shift stages each comprise a  
25 first MEMS-based device having a moveable mirror layer operable to experience a substantially piston-like motion in response to a control signal.

068069.0110

110

19. The apparatus of Claim 18, wherein the first MEMS device comprises:

an inner conductive layer disposed inwardly from the moveable mirror layer and forming a space between the  
5 moveable mirror layer and the inner conductive layer;

wherein the moveable mirror layer comprises an at least substantially conductive layer operable to move relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and  
10 the inner conductive layer.

20. The apparatus of Claim 19, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror  
15 strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

21. The apparatus of Claim 20, wherein all of the  
20 moveable mirror strips move at least substantially in unison in response to the voltage difference.

068069.0110



111

22. A wave division add/drop multiplexer,  
comprising:

a wavelength division demultiplexer operable to  
separate an optical input signal into a plurality of  
5 wavelengths;

an array of optical add/drop multiplexers coupled to  
the demultiplexer, at least one of the add/drop  
multiplexers comprising:

10 a drop phase shift stage operable to receive an  
input wavelength and to either drop the input  
wavelength or to pass the input wavelength toward an  
output, the drop phase shift stage comprising an at  
least substantially reflective surface operable to  
change its position to affect whether the input  
15 wavelength is dropped or passed to the output; and

an add phase shift stage operable to receive  
and communicate as an output either an added  
wavelength or the input wavelength passed from the  
drop phase shift stage, the add phase shift stage  
20 comprising an at least substantially reflective  
surface operable to change its position to affect  
whether the added wavelength or the input wavelength  
is passed to the output; and

a wavelength division multiplexer operable to  
25 receive a plurality of output wavelengths from the add  
phase shift stage and to multiplex at least some of the  
output wavelengths into an optical output signal.

0574683 12200

23. The wave division add/drop multiplexer of Claim 22, wherein at least one of the at least substantially reflective surfaces comprises a moveable mirror layer of a micro-electro-optic system (MEMS) device operable to  
5 undergo a substantially piston-like motion to change its position.

24. The wave division add/drop multiplexer of Claim 22, further comprising a bypass path coupled between the  
10 wavelength division demultiplexer and the wavelength division multiplexer, the bypass path operable to communicate at least one wavelength directly between the demultiplexer and the multiplexer without processing the at least one wavelength.

002227 22224650

113

25. A wave division add/drop multiplexer,  
comprising:

a wavelength division demultiplexer operable to  
separate an optical input signal into a plurality of  
5 wavelengths;

an array of optical add/drop multiplexers coupled to  
the demultiplexer, at least one of the add/drop  
multiplexers comprising:

an input operable to receive an input  
10 wavelength signal and an added wavelength signal,  
and to generate a first and a second copy of the  
input signal and a first and a second copy of the  
added signal;

a plurality of at least substantially  
15 reflective surfaces, each operable to receive either  
the first signal copies or the second signal copies  
and to reflect the copies for ultimate combination  
at an output to form an output signal for  
transmission, at least one of the at least  
20 substantially reflective surfaces comprising a  
moveable mirror operable to change its position  
relative to the input to create a phase shift  
between the first and second signal copies so that  
either the input optical signal or the added optical  
25 signal is communicated as the output signal  
depending on the position of the at least one  
moveable mirror; and

a wavelength division multiplexer operable to  
receive a plurality of output signals from the array of  
30 add/drop multiplexers and to multiplex at least some of  
the output wavelengths into an optical output signal.

002227 "22224260  
0974633 12200

26. A wave division add/drop multiplexer,  
comprising:

5 a wavelength division demultiplexer operable to  
separate an optical input signal into a plurality of  
wavelengths;

10 an array of optical add/drop multiplexers coupled to  
the demultiplexer, at least one of the add/drop  
multiplexers comprising a micro-electro-optic system  
(MEMS) device comprising a moveable mirror layer operable  
to undergo a substantially piston-like motion to create a  
phase difference between a wavelength reflected from the  
moveable mirror layer and a substantial copy of that  
wavelength, the position of the moveable mirror layer  
affecting whether the input wavelength is passed through  
15 or dropped from the array; and

a wavelength division multiplexer operable to  
receive a plurality of output wavelengths from the array  
and to multiplex at least some of the output wavelengths  
into an optical output signal.

09/15/2013 13:30:00 "2284460"

115

27. A method of facilitating optical add/drop multiplexing, comprising:

receiving an input optical signal and an added optical signal;

5 generating a first and a second copy of the input signal;

generating a first and a second copy of the added signal;

10 communicating the first signal copies toward a first mirror and the second signal copies toward the second mirror;

changing the position of the first mirror to create a phase shift between the first and second copy when combined at an output; and

15 communicating either an added signal or the input signal as an output signal depending at least in part on the position of the first mirror.

28. The method of Claim 27, wherein the first  
20 mirror comprises a micro-electro-optic system (MEMS) device having a moveable mirror layer operable to experience a substantially piston-like motion in response to a control signal.

002221 22394750

wherein changing the position of the moveable mirror layer comprises displacing the moveable mirror layer relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and the inner conductive layer.

30. The method of Claim 29, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

31. The method of Claim 30, wherein changing the  
20 position of the moveable mirror layer comprises  
displacing all of the moveable mirror strips relative to  
the inner conductive layer substantially in unison in  
response to the voltage difference.

25           32. The method of Claim 30, wherein changing the  
position of the moveable mirror layer comprises:

coupling either the inner conductive layer or each of the moveable mirror strips to a ground; and applying to the other a control voltage signal.

33. The method of Claim 29, wherein changing the position of the moveable mirror layer comprises selectively displacing the moveable mirror layer relative to the inner conductive layer, wherein the distance increases as the voltage difference between the moveable mirror layer and the inner conductive layer increases.

Variable	Mean	SD	Min	Max
Age (years)	45.2	12.5	25	65
Gender (Male/Female)	55/45			
Education (years)	12.8	2.1	8	16
Income (USD/month)	1,200	300	500	2,500
Marital status (Married/Single)	70/30			
Health status (Good/Fair/Poor)	60/20/20			
Smoking status (Smoker/Non-smoker)	30/70			
Alcohol consumption (Yes/No)	15/85			
Exercise frequency (times/week)	2.5	1.5	0	5
Stress level (Low/Medium/High)	40/30/30			
Sleep quality (Good/Fair/Poor)	50/30/20			
Dietary habits (Healthy/Unhealthy)	60/40			
Family size (number of members)	3.2	1.2	1	6
Work status (Employed/Unemployed)	75/25			
Health insurance (Yes/No)	90/10			
Chronic diseases (Hypertension/Diabetes)	20/10			
Medication use (Yes/No)	30/70			
Healthcare utilization (times/year)	2.0	1.0	0	5
Healthcare satisfaction (Satisfied/Dissatisfied)	60/40			
Healthcare accessibility (Easy/Difficult)	50/50			
Healthcare quality (Good/Fair/Poor)	60/30/10			
Healthcare cost (Low/Medium/High)	40/30/30			
Healthcare coverage (Full/Partial/None)	70/20/10			
Healthcare provider (Physician/Nurse)	80/20			
Healthcare facility (Hospital/Outpatient)	60/40			
Healthcare service (Consultation/Medication)	70/30			
Healthcare outcome (Improved/Not improved)	60/40			
Healthcare recommendation (Yes/No)	80/20			
Healthcare feedback (Positive/Negative)	70/30			
Healthcare evaluation (Excellent/Good/Fair/Poor)	20/40/30/10			
Healthcare improvement (Yes/No)	60/40			
Healthcare innovation (Yes/No)	30/70			
Healthcare research (Yes/No)	20/80			
Healthcare education (Yes/No)	40/60			
Healthcare training (Yes/No)	50/50			
Healthcare development (Yes/No)	60/40			
Healthcare progress (Yes/No)	70/30			
Healthcare future (Bright/Dark)	60/40			
Healthcare vision (Clear/Unclear)	70/30			
Healthcare mission (Clear/Unclear)	80/20			
Healthcare vision statement (Yes/No)	90/10			
Healthcare mission statement (Yes/No)	80/20			
Healthcare vision statement (Yes/No)	70/30			
Healthcare mission statement (Yes/No)	60/40			
Healthcare vision statement (Yes/No)	50/50			
Healthcare mission statement (Yes/No)	40/60			
Healthcare vision statement (Yes/No)	30/70			
Healthcare mission statement (Yes/No)	20/80			
Healthcare vision statement (Yes/No)	10/90			
Healthcare mission statement (Yes/No)	0/100			

receiving an optical input signal at a first stage;  
generating a first and a second copy of the input  
5 signal;

communicating either an added signal or the input  
10 signal from the first stage toward a second stage  
depending at least in part on the position of the first  
mirror;

15           communicating the first received signal copy toward  
a third mirror and the second received signal copy toward  
a fourth mirror; and

35. The method of Claim 34, wherein the first mirror comprises a micro-electro-optic system (MEMS) device having a moveable mirror layer operable to experience a substantially piston-like motion in response to a control signal.



36. The method of Claim 35, wherein the MEMS device comprises an inner conductive layer disposed inwardly from the moveable mirror layer and forming a space between the moveable mirror layer and the inner  
5 conductive layer; and

wherein changing the position of the moveable mirror layer comprises displacing the moveable mirror layer relative to the inner conductive layer in response to a voltage difference between the moveable mirror layer and  
10 the inner conductive layer.

37. The method of Claim 36, wherein the moveable mirror layer comprises a plurality of adjacent mirror strips, at least some of the plurality of adjacent mirror  
15 strips separated by air gaps operable to relieve air damping when the mirror strips move relative to the inner conductive layer.

38. The method of Claim 37, wherein changing the  
20 position of the moveable mirror layer comprises displacing all of the moveable mirror strips relative to the inner conductive layer substantially in unison in response to the voltage difference.

120

39. A method of facilitating wave division add/drop multiplexing, comprising:

receiving an optical input signal comprising a plurality of wavelengths;

5 separating the optical signal into a plurality of wavelength signals;

communicating at least some of the wavelength signals to an array of optical add/drop multiplexers;

at at least one of the add/drop multiplexers:

10 receiving an input optical signal and an added optical signal;

generating a first and a second copy of the input signal;

15 generating a first and a second copy of the added signal;

communicating the first signal copies toward a first mirror and the second signal copies toward the second mirror;

20 changing the position of the first mirror to create a phase shift between the first and second copy when combined at an output; and

communicating either an added signal or the input signal as an output signal depending at least in part on the position of the first mirror.

09746823 133000  
002227 228460

121

40. A method of facilitating wave division add/drop multiplexing, comprising:

receiving an optical input signal comprising a plurality of wavelengths;

5 separating the optical signal into a plurality of wavelength signals;

communicating at least some of the wavelength signals to an array of optical add/drop multiplexers;

at at least one of the add/drop multiplexers:

10 receiving an optical input signal at a first stage;

generating a first and a second copy of the input signal;

15 communicating the first signal copy toward a first mirror and the second signal copy toward the second mirror;

changing the position of the first mirror to create a phase shift between the first and second copy when combined at an output of the first stage;

20 communicating either an added signal or the input signal from the first stage toward a second stage depending at least in part on the position of the first mirror;

25 generating a first and a second copy of the signal received at the second stage;

communicating the first received signal copy toward a third mirror and the second received signal copy toward a fourth mirror;

09746832 13300  
00000000 00000000

122

changing the position of the third mirror to create a phase shift between the first and second received signal copies when combined at the second output; and

- 5        communicating either the added signal or the input signal from the first stage from the second output depending at least in part on the position of the third mirror.

09/16/2011 12:23:00

123

41. An apparatus operable to facilitate add/drop multiplexing of optical signals, the apparatus comprising:

an input operable to receive an input optical signal  
5 and an added optical signal, and to generate a first and a second copy of the input signal and a first and a second copy of the added signal;

a plurality of at least substantially reflective surfaces, each operable to receive either the first  
10 signal copies or the second signal copies and to reflect the copies for ultimate combination at an output to form an output signal for transmission, at least one of the at least substantially reflective surfaces comprising a Micro-electro-optic system (MEMS) device comprising a  
15 plurality of adjacent mirror strips, the mirror strips operable to change their position substantially in unison in a substantially piston-like motion relative to the input to create a phase shift between the first and second signal copies so that either the input optical  
20 signal or the added optical signal is communicated as the output signal depending on the position of the at least one moveable mirror.

09746822 122000

124

42. A method of facilitating optical add/drop multiplexing, comprising:

receiving an input optical signal and an added optical signal;

5 generating a first and a second copy of the input signal;

generating a first and a second copy of the added signal;

communicating the first signal copies toward a first  
10 mirror and the second signal copies toward the second mirror, the first mirror comprising a plurality of adjacent mirror strips operable to receive the first signal;

displacing adjacent mirror strips substantially in  
15 unison in a substantially piston-like motion to create a phase shift between the first and second copy when combined at an output; and

communicating either an added signal or the input  
signal as an output signal depending at least in part on  
20 the position of the adjacent mirror strips.

002221 2234250